


## CONNECTORS

### Push Type Wire Connectors



New type connectors that let you push wires into contact for a positive copper-to-copper connection without twisting or taping. Test holes in the front and back of the connectors accept round or flat probes of test equipment to facilitate troubleshooting.

Auveco Part No.	No. of Wires	Gauge	Rated Voltage	Color	Unit Pkg.
15845	3	22-16	300	Gray	25
15849	4	18-12	600	Blue	25



### Wire Nut® Connectors

10378 UNIT PACKAGE: 25  
15204 UNIT PACKAGE: 100  
Gray

Joins 18 & 16 Ga. Wires  
Minimum of 2 #18 Ga. Wires  
Maximum of 2 #16 Ga. Wires

10379 UNIT PACKAGE: 25  
15205 UNIT PACKAGE: 100  
Blue

Joins 18-14 Ga. Wires  
Minimum of 2 #18 Ga. Wires  
Maximum of 3 #16 Ga. Wires

10380 UNIT PACKAGE: 25  
15206 UNIT PACKAGE: 100  
Orange


Joins 18-14 Ga. Wires  
Minimum of 2 #18 Ga. Wires  
Max. of 3 #16 Ga & 1 #18 Ga. Wires

10381 UNIT PACKAGE: 25  
15207 UNIT PACKAGE: 100  
Yellow

Joins 18-12 Ga. Wires  
Min. of 1 #14 Ga. & 1 #18 Ga. Wires  
Max. of 2 #14 Ga. & 3 #16 Ga. Wires

10382 UNIT PACKAGE: 25  
15208 UNIT PACKAGE: 100  
Red

Joins 18-10 Ga. Wires  
Min. of 1 #12 Ga. & 2 #18 Ga. Wires  
Max. of 2 #10 Ga. & 1 #12 Ga. Wires



### Wing Wire Nut® Connectors

10384 UNIT PACKAGE: 25  
15209 UNIT PACKAGE: 50  
Blue

Joins 14-6 Ga. Wires  
Minimum of 1 #10 Ga. & 1 #12 Ga. Wires  
Max. of 1 #6 Ga. & 2 #8 Ga.

15705  
Yellow

Joins 22-12 Ga. Wires  
Minimum of 2 #18 Ga. Wires  
Maximum of 2 #12 Ga. Wires

UNIT PACKAGE: 50


15706  
Red

Joins 20-8 Ga. Wires  
Min. of 2 #16 Ga. Wires  
Max. of 4 #12 Ga. Wires

UNIT PACKAGE: 50

### Wing Wire Connectors

Combines both the wide range and torque of wing-style connectors with a new flexible skirt that provides over-strip protection without taking additional space in the electrical box.



18312

Orange & Blue

Joins from two 22 ga.  
to two 12 ga. wires

UNIT PACKAGE: 25