

## Sec. 12

### Sealed Fuse Holders For ATM Mini® Fuses

Not Actual Size



**20206**

20, 25 & 30 Amp Capacity  
10" Long 12 Ga. Cross-Linked  
Polyethylene Leads  
Fuse Not Included

UNIT PACKAGE: 1

**20207**

2-15 Amp Capacity  
10" Long  
16 Ga. Cross-Linked  
Polyethylene Leads  
Fuse Not Included

UNIT PACKAGE: 1

### High Power Sealed Fuse Holder



**20320**

For ATC & ATO Fuses  
40 Amp Capacity  
12" Long 10 Gauge 105 Strand  
EZ Flex Wire Leads  
Fuse Not Included

UNIT PACKAGE: 1

### Environmentally Sealed Blade Type Fuse Holder

Also Used As Fuel Pump Fuseholder on GM Vehicles  
(Fuse Not Included)



**13686**

(GM: 12101917; Delco: PT-189)

Unit Pkg: 1

Electrical system protection for fleets, construction equipment, aircraft service vehicles, outdoor power equipment and marine installations.

Resistant to moisture, salt spray and engine compartment fluids. Withstands 50 g physical shock. Operating temperature range from -40° to 125°C.

- Nylon Body with Latching Cap
- Silicone Rubber Seals at Wires and Cap
- 12 Gauge SE/GPT Wire Leads
- 3 to 30 Amp Capacity - Type ATC/ATO Fuses
- 5" Long Wire Leads