ROUTING CLIPS



Nylon Cable Clips

Auveco Part No.	Cable Size	Screw Size	Unit Pkg.
13939	3/16"	#8-10	50
13940	1/4"	#8-10	50
13941	5/16"	#8-10	50
13944	1/2"	#8-10	50



5ec. 13

13937 Nylon Spring Clip Width: 3/8" Overall Length: 1-5/16" Thickness: .060 Use w/#8 Screw UNIT PACKAGE: 50

Cable Clips For Co-Ax Cable Polyethylene clips with corrosion resistant galvanized steel nail.



(l Jam N	ſ
/eco t No.	Range	U P
	E/22" to 1/4"	

Auv nit Part 'kg. 100575/32" to 1/4"10 100585/16" to 1/2"10

100599/16" to 3/4"10


3/16"-9/32" Cable Dia. Nail Length: 1"


15854

UNIT PACKAGE: 50

Strain-Relief Cable Connector

Reliable, liquid-tight, nylon strain-relief cable connector for quick and easy installation. They do not have to be disassembled before using. Simply insert a cable into the connector, tighten the cap nut and the cable is automatically fixed, centered, sealed and strain relieved.





Auveco Part No.	Wire Dia.	Thread	Thread Length (Bottom)	Hex	Unit Pkg.
15851	.236"472"	1/2" NPT	.512"	.945"	5

© Copyright 2008, Au-ve-co Products Co.

"SINCE 1916" *THE* COMPLETE FASTENER LINE 217

www.clipsandfasteners.com