

MISCELLANEOUS ITEMS

KNOBS

Black Thermoplastic Material • Zinc Plated Steel Studs & Inserts



Auveco Part No.	Thread Size	Stud Length	Head O.D.	Unit Pkg.
18959	1/4"-20	1"	1-3/4"	5
18960	5/16"-18	1-1/2"	1-3/4"	3

Auveco Part No.	Internal Thread Size	Head Size	Unit Pkg.
18962	5/16"-18	11/16" x 2"	5



Auveco Part No.	Thread Size	Stud Length	Head Size	Unit Pkg.
18965	5/16"-18	1-1/2"	11/16" x 2"	3

Auveco Part No.	Thread Size	Stud Length	Wing Span	Unit Pkg.
18969	1/4"-20	1/2"	1-3/4"	5



Shaft Collars

Precision machined from cold finished steel. Equipped with cup point socket set screws. Zinc plated finish.



Auveco Part No.	Bore (I.D.)	O.D.	Width	Set Screw Size	Unit Pkg.
15837	1/4"	1/2"	5/16"	#10 x 1/8"	5
15838	3/8"	3/4"	3/8"	1/4" x 3/16"	5
15839	1/2"	1"	7/16"	1/4" x 1/4"	5
15840	5/8"	1-1/8"	1/2"	5/16" x 1/4"	5
15841	3/4"	1-1/4"	9/16"	5/16" x 1/4"	5
15843	1"	1-5/8"	5/8"	5/16" x 5/16"	2



Clear Flexible Vinyl (PVC) Tubing

Our tubing has a broad range of chemical resistance to acids, alkalies and solvents. It's ideal for use in industrial air pressure line applications, in the food industry (FDA approved), for potable water, and for various gases and chemicals.



Auveco Part No.	I.D.	O.D.	Wall Thickness	*Maximum Suggested Working Pressure (PSI @ 70° F)	Unit Package Quantity
14801	1/8"	1/4"	1/16"	59	100 Ft.
14802	3/16"	5/16"	1/16"	51	100 Ft.
14803	1/4"	3/8"	1/16"	51	100 Ft.
14804	5/16"	7/16"	1/16"	48	100 Ft.
14805	3/8"	1/2"	1/16"	41	100 Ft.
14806	3/8"	5/8"	1/8"	55	100 Ft.
14807	1/2"	5/8"	1/16"	28	100 Ft.
14808	1/2"	3/4"	1/8"	41	100 Ft.

*We recommend verification by testing of the size and material to be used.