

Aluminum Oxide Resin Bonded Cut-Off Wheels

Designed for steel cutting use only. Never use these wheels for any other applications.
Never Use On Fiberglass!

Auveco Part No		SPECIFICATIONS				
Unit Pkg. 10	Unit Pkg. 25	Dia.	Thickness	Arbor	Grit	RPM
19688	19687	3"	1/16"	3/8"	54	25,000
19690	19689	3"	1/32"	3/8"	54	25,000
19692	19691	3"	1/16"	1/4"	54	25,000
19694	19693	3"	1/32"	1/4"	54	25,000
19696	19695	3"	1/8"	1/4"	46	25,000
19698	19697	3"	1/8"	3/8"	46	25,000
19700	19699	4"	3/32"	5/8"	46	15,300
19702	19701	4"	1/32"	3/8"	60	21,000
19704	4"	1/32"	5/8"	60	21,000
19706	19705	4"	1/16"	3/8"	54	21,000
19708	19707	4"	1/8"	3/8"	46	15,300



General Purpose Depressed Center Wheels

TYPE 27

Standard Shape

The most popular Raised Hub wheel for grinding and blending

CAUTION!

Never Use A Wheel That Has Been Dropped

- Always Wear Full Face Protection When Grinding
- Use A Guard Covering 50% Or More Of Wheel Diameter



Auveco Part No		SPECIFICATIONS				
Unit Pkg. 10	Unit Pkg. 25	Dia.	Width	Arbor	Grit	RPM
19712	19711	4"	1/4"	5/8"	36	13,700
19714	19713	4-1/2"	1/4"	7/8"	24	11,900

Cut-Off Wheel Mandrels (Arbors For Air Grinders)

Not Actual Size



19715
Zinc

Mandrel With
3/8" Shoulder Screw
UNIT PACKAGE: 1



19716
Zinc

Mandrel With
1/4" & 3/8" Shoulder Screws
UNIT PACKAGE: 1



Welding Blanket

21083

A 6 ft. x 6 ft. lightweight, welding blanket to protect from the spray of sparks, spatter and slag. Our fire and heat resistant welding blankets are made with a carbon fiber fabric that was developed from NASA technologies. The carbon fibers can withstand temperatures of 1800°F from contact with hot metal, for short durations but should not be exposed to temperatures of 200° F for extended periods. The blankets are easy to clean; just shake, vacuum or use compressed air to blow metal particles out.

UNIT PACKAGE: 1